



BUDDY RHODES CONCRETE PRODUCTS
LIQUID COLOR
PRODUCT DATA SHEET

Liquid Color

Buddy Rhodes Liquid Colors are water based, high solid, iron oxide pigments designed specifically for use with the Buddy Rhodes Concrete Mix. Liquid pigments allow the color to distribute uniformly throughout the mix, ensuring proper color disbursement for rich, intense and consistent color. Buddy Rhodes Liquid Colors will not fade or streak. Convenient packaging allows the Buddy Rhodes Liquid Color to be added directly into the mix water. One jar is formatted to color two bags (140 lbs) of concrete counter mix, yielding approximately 9 square feet of concrete countertop at 1.5" of thickness. Buddy Rhodes Liquid Color is available in fourteen standard colors with more color selections to come.

The liquid color will color other concrete mixes, mortars, grouts, and plasters, but results will vary. Always make a test sample.

Mixing Instructions

Because Buddy Rhodes Counter Mix is bone white, it takes color very well. Water requirements for the mix vary due to weather, geographical region, and desired finish. So, it is best to start with a minimum amount of water and add until the proper feel is reached. Each bag of mix will use at least 1 gallon of water, so let's begin there.

- 1) Measure out 1 gallon of water for each bag of mix being used.
- 2) Shake color and add to mix water. (Remember: 1 jar of color is good for 2 bags, so 1 jar of color will go into 2 gallons of mix water at this step.) Get all the color out of the jar and rinse jar into mix water if necessary. Stir the water and dissolve the color as completely as possible.
- 3) Add mix water with color to counter mix and incorporate well.
- 4) Add additional water 1 quart at a time until desired consistency is achieved. (Go for the feel of dry oatmeal for a pressed finish and cream of wheat for a trowelled finish.)

Cure Time

The color of a concrete counter will change as the slab cures. Allow at least three days before sealing to achieve the final color.



BUDDY RHODES CONCRETE PRODUCTS
LIQUID COLOR
PRODUCT DATA SHEET

WARNING

<p>Not a hazardous material.</p>	<p>FIRST AID: Should contact with eyes occur, flush with water for at least 15 minutes. Seek medical attention. In case of adverse reaction with skin, wash exposed skin with soap and water until gone. Discontinue use at once. Get medical advice as deemed appropriate. If inhaled, remove individual to fresh air, get medical attention at once if there is any discomfort. If ingested: if conscious, give large quantities of water to induce vomiting. Get medical attention.</p> <p>KEEP OUT OF REACH OF CHILDREN.</p>
----------------------------------	--

LIMITED WARRANTY

<p>This product is suitable for only the purpose intended when used in accordance with the instructions. No guarantee of results is made where conditions are beyond our control. No representations either expressed or implied are made with respect to the product except as herein stated. Liability is limited to the replacement of this product or reimbursement of purchase price only if material is found to be defective.</p>	<p>This Limited Warranty is issued and accepted in lieu of all other express warranties and expressly includes liability for consequential damages.</p>
--	---