



BUDDY RHODES CONCRETE PRODUCTS
SATIN CONCRETE SEALER
PRODUCT DATA SHEET

Buddy Rhodes Satin Concrete Sealer is the latest in water based acrylic micro emulsion technology for concrete countertops. It creates a barrier coating that seals and protects while enhancing the natural beauty of the concrete. The sealer will resist most stains up to 72 hours; however, oils and solvents should be wiped up promptly.

For Uses On

- All concrete and masonry surfaces
- Exposed aggregate
- Stamped and colored concrete
- Natural and manufactured stone brick
- Concrete paver tiles

Buddy Rhodes Satin Concrete Sealer is ideal for cooking and eating areas to protect surfaces against food and beverage stains.

Limitations

Not recommended for marble, granite, or porcelain.

Preparation

Surface should be completely clean and dry (at least 24 hours for curing concrete). If using the Buddy Rhodes Penetrating Sealer first (highly recommended), try to apply the Satin Sealer as soon as the surface is dry to the touch and within 1 hour.

Application

Buddy Rhodes Satin Concrete Sealer can be applied by at least two methods:

- 1) **Apply with a cotton rag:** For approximately two square feet of counter, pour a teaspoon of sealer directly onto the surface and rub it into the counter with a dry white cotton rag. Work quickly and steadily. Continue to rub with rag while the sealer dries until a dull luster is achieved. Hand buff any remaining brush strokes with a fine synthetic steel wool pad.
- 2) **Apply with a 4" foam brush:** Pour sealer into a shallow container. Dip just the tip of the brush in sealer and brush out 3-4 light layers. Avoid pooling the sealer. Hand buff surface with fine synthetic steel wool pad between coats to smooth any brush strokes.

Multiple Coats and Water Penetration Test

Always test a small area to assure repellency and satisfaction of appearance. A simple penetration test is to sprinkle water on the surface. If water penetration occurs or if water does not bead up on the surface, continue with additional coats. The process of coating and testing should be performed until beading is achieved. Continued application after beading is not recommended.



BUDDY RHODES CONCRETE PRODUCTS
SATIN CONCRETE SEALER
PRODUCT DATA SHEET

WARNING

<p>Proposition 65 – State of California This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm. This product contains crystalline silica, which is a dust. Respiratory or health problems may result if inhaled, or cancer may result from continued inhalation. Please wear respiratory, eye and body protection when using this Product.</p>	<p>Liquid contact with eyes and skin causes irritation. Do not ingest. Contains ethylene glycol ethyl hexyl ether, CAS# 1559-35-9 and propylene glycol monobutyl ether, CAS# 2131-66-8. Avoid contact with eyes and skin. Wash hands thoroughly after using and before eating and smoking. If spillage has occurred, absorb and dispose of according to local regulations.</p> <p>Should eye contact occur, flush with plenty of water for at least 15 minutes and get medical attention if vision is disturbed. For skin, wash thoroughly with soap and water. If swallowed, get medical attention immediately. DO NOT induce vomiting.</p> <p>KEEP OUT OF REACH OF CHILDREN.</p>
---	---

LIMITED WARRANTY

<p>This product is suitable for only the purpose intended when used in Accordance with the instructions. No guarantee of results is made where conditions are beyond our control. No representations either expressed or implied are made with respect to the product except as herein stated. Liability is limited to the replacement of this product or reimbursement of purchase price only if material is found to be defective.</p>	<p>This Limited Warranty is issued and accepted in lieu of all other express warranties and expressly includes liability for consequential damages.</p>
--	---